

## 1. PRODUCT NAME

American Soffit Liner panels.

## 2. MANUFACTURER

### AMERICAN BUILDINGS COMPANY

1150 State Docks Road  
Eufaula, Alabama 36027  
Phone: (334) 687-2032

## 3. PRODUCT DESCRIPTION

These panels have a configuration consisting of 1" interlocking ribs. The interlocking ribs are designed to conceal the panel fasteners. The panel provides a net coverage of 12".

**Basic Use:** A soffit covering for new or retrofit construction.

**Materials:** Soffit Liner panels are available in 24 gage, 50,000 psi G90 zinc-coated (galvanized), AZ50 aluminum-zinc alloy-coated steel or 0.032 aluminum (Regal White only). Panels have American Buildings Company's SmartKote® (PVDF) Finish.

## 4. TECHNICAL DATA

See "Panel Profile" Below.

## 5. INSTALLATION

Installation should be performed in accordance with American Buildings Company's manuals and building erection drawings, and should be by a qualified installer using proper tools and equipment. Systems are installed by American Buildings Company Authorized Builders.

## 6. AVAILABILITY

For availability, contact:

**AMERICAN BUILDINGS COMPANY**

## 7. WARRANTY

Thirty-five year material warranties are available.

## 8. MAINTENANCE

Only normal routine maintenance is required over the life of the panels.

## 9. TECHNICAL SERVICES

For information, contact:

**AMERICAN BUILDINGS COMPANY**

## 10. PRODUCT NOTES

A certain amount of waviness called "oilcanning" may exist in this panel. Minor waviness of the panel is not sufficient cause for rejection, because oilcanning does not affect the structural integrity of the panel.

American Buildings Company reserves the right to revise all standard specifications and information. American Buildings Company regularly updates its published "Standard Specifications" on the American Buildings web site, [www.americanbuildings.com](http://www.americanbuildings.com), which supercede and replace any previously published standard specifications of American Buildings Company.

